5. 6740-242-9175 Print washer, photo., max print size, 11 in. wd, lk in. long, 115 v, Sig type PH-240-A.

3416-186-4061 Lathe, eng. bench mtg., solid bed, 3/4 hp, 220 v, AC, 60 cyc, 3 ph (RS 8100-440000).

- 2 -

7. 3419-223-1982 Grinding and buffing machine, utility floor mtg., 5/8 in. spindle, 1/2 hp, 110-220 v, AC, 60 eye, s ph (RS 8100-334500).

8. 3413-529-0812 Drilling machine, upright, floor mounting, 5/8 in. drill cap., 1/2 hp, 220 v, AC, 60 cyc, 3 ph, 345-3205 rpm.

9. Milling machine, equivalent to Bridgeport
Milling Machine Model "J", 220 v, AG, 3 ph,
60 cyc, 9" x 32" table.
R-8 Spindle taper.
1 set collets 1/8 through 3/4
#1 Bridgeport 5" swivel vise.
#5 Bridgeport Right Angle Attach.
#2 Bridgeport Offset boring head
Cross travel stop
#1, #2, #3 shell mill holders R8 shank
#14 Jacobs Precision Drill Chuck

We would be everly optimistic to presume that our list is at present a complete one and will be pleased to discuss substitutions with you for any items which might not now be available. We plan to submit additional requirements in summary lists as soon as these lists are established.

Items 1 through 5 are repeated under Processing Equipment and Items 6 through 9 under Maintenance Equipment in the equipment breakdown lists.

Yours very truly,

______25X1A

25X1A

ELG: BLE: LB Enc. ce: DK BLE

LEW

Equipment Component List Photographic Laboratory & Shop

25X1A

25X1A

The following items are required by March 1, 1961. Ship and hold all A quantity of one each is desired except wherein noted following the stock identification number.

Soldering Iron - Electric thermostatically cont 110 v AC 60 cyc w/o tips Clamp - Parallel toolmakers 2 in. Vise, bench and mach table, jaw, 2 in.
Clamp - Parallel toolmakers 2 in. Vise, bench and mach table, jaw, 2 in.
Faceshield, industrial, plas mask
Goggles, industrial, frame one-piece single apert, plas, clear, ventilated, w/clear plas lens, polarized, w/o carrying case (pr)
Compressor, reciprocating, power dr, air, 2 stages, 5.3 cfm piston displacement, 100 psi dischg press., mtr, 1 ph, AC, air rec tank, mtd
Oiler, hand, compressible surf. fed, 8 oz cap., 7 in. lg spout
Shears, metal, cutting, hand, str
Chisel, cold, hand, 1/2 in.
Cutter, glas, line cutting type, wheel type cutting end
Frame - Hacksaw 10-12 in. adj
Frame, jeweler's saw, adj, 2-1/2 in. throat d
Chisel, cold, hand, 1/4 in. wd cut
Shears, bent trimmers, 10 in. grade 2
Drill, breast, w/spirit level, 0 to 3/8 in. cap
Stripper, wire, hand, w/auto. stop, 8-22 AWG and AN cap.
Screwdriver, flat tip, wood handle, 1-1/2 in. lg blade
Screwdriver - Common w/screw holding att 1gth of blade 4 in. approx 7/32 in. wd
Clamp - C lt serv 3 in.
Clamp, C, 6 in., 2-3/4 in. d throat, lt serv
Socket, socket wrench, d style, sq dr 3/8 in., 12 point, 7/16 in. size
Socket - 12 point 3/8 in. sq dr 3/8 in. deep
Socket - Universal 12 point 3/8 in. sq dr 3/8 in. BO
Wrench, torque, L handle, sq male dr, 25 in. cap.
Screwdriver, flat tip, metal handle, 4 in. 1g blade
Extractor, screw, str fluted, w/sliding nut, 1/4 in. screw size rating, No. 1
Extractor, screw str fluted, w/sliding nut, 5/16 in. screw size rating, No. 2
Extractor, screw, str fluted, w/sliding nut, 3/8 in. screw size rating, No. 3
Pliers, slip joint, str nose, comb., w/cutter, 10 in.
Vise, pin, .000 to .040 in.
Universal joint, socket wrench, sq end, 3/8 in.
Socket, socket wrench, sq dr 3/8 in., 12 point, 9/16 in. sise
Socket - 12 point 3/8 in. sq dr 3/4 in.
Ratchet attachment, socket wrench, reversible, sq end 3/8 in.

Charlie Doc has a copy of this lesting broken down into
categories: Approved For Release 2002/16/16: CIA-RDP67B00511R000100140065/5
neld it that way

Stock No.	Description
5120-232-5706	Socket, socket wrench, sq dr 3/8 in., 12 point, 11/16 in.
	size
5120-236-2139	Screwdriver - Cabinet str tip 5 in. 1g blade 3/16 in. wd
	tip rd blade plas handle
5120-237-0977	Socket - 12 point 3/8 in. sq dr 1/2 in.
5120-237-0978	Socket - Universal 12 point 3/8 in. sq dr 9/16 in. BO
5120-237-0979	Socket - Universal 12 point 3/8 in. sq dr 11/16 in.
5120-237-0980	Socket - Universal 12 point 3/8 in. sq dr 3/4 in. BO
5120-237-4969	Handle, socket wrench, brace, 3/8 in. dr end
5120-237-4973	Socket - 12 point 3/8 in. sq dr 5/8 in.
5120-237-4974	Socket - Universal 12 point 3/8 in. sq dr 5/8 in. BO
5120-237-6985	Screwdriver - common lgth of blade 8 in. a prox 3/8 in. wd.
*	.050 in. thk
5120-240-5328	Wrench, open end, adj, single hd, & in. 1g
5120-240-5330	Wrench, open end, adj, single hd, h in. lg
5120-240-5364	Handle, socket wrench, ratchet, 3/8 in.
5120-240-5396	Handle - Socket wrench hinge 3/8 in. sq dr
5120-240-7308	Block, bench, mechanics, steel, 3 in. dia.
5120-241-3143	Handle, socket wrench, sliding "T", 3/8 in. dr end
5120-241-3185	Socket - 12 point 3/8 in. sq dr 1/2 in. deep
5120-242-3352	Socket - Universal 12 point 3/8 in. sq dr 1/2 in BO
5120-242-3354	Socket - Universal 12 point 3/8 in. sq dr 7/16 in. BO
5120-243-1348	Vise, pin., .025 to .062 in.
5120-243-1689	Extension, socket wrench, 3/8 in. sq shape end, 3 in. lg
5120-243-1690	Extension, socket wrench. 3/8 in. so shape end. 8 in. 1s
5120-263-3458	Tweezers, craftsman's, hollow jaw, 4-3/4 in.
5120-273-9203	Extension, socket wrench, 3/8 in. sq shape end, 5 in. 1g
5120-277-4063	Wrench, tap and reamer, adj, 1/16 to 1/4 in.
5120-293-0045	Pliers, ret ring, intr, flat jaws, str tips, w/brkt, 5000
	ring series, 106-175 size range
5120-293-0046	Pliers, ret ring, intr, flat jaws, str tips, w/brkt, 5000
	ring series, 181-350 size range
5120-293-0048	Pliers, ret, ring, intr, flat jaws, str tips, w/brkt, 5000
	ring series, 37-102 size range
51.20-293-0049	Pliers, ret. ring, ext, flat jaws, str tips, w/brkt, 5100
	ring series, 93-143 size range
5120-293-2251	Wrench, spanner, adj, 13/32 in. thk of hook, 1-1/4 to a-1/2
	in. dia. range, nonsparking and nonmagnetic
5120-293-3481	Pliers - Long needle nose non-side cutting 6-1/2 in lg
5120-299-8412	Pliers, optician's, hollow chop
51.20-534-0473	French - Spanner camera lens adj univ type D-1
5120-555-2088	Screwdriver - Common 1gth of blade 6 in. approx 5/16 in. wd
73.50 FAF	.046 in. thk
5120-595-9073	Wrench, torque, L handle, sq male dr, 3/4 in. dr 100 to
1100 for ere/	750 in. 1b cap.
5120-595-9526	Pliers, ret. ring ext, flat jaws, str tips, w/brkt, 5100
£130 203 1394	ring series, 0.37 to 0.87 size range
5130-293-1386	Drill, elec, port., str dr, hwy duty, 1/4 in., 2000 rpm,
E130 202 1910	AC, DC 115 v, end handle w/closed grip
5130-293-1849	Drill, elec, port., hvy duty, 1/2 in., 650 rpm, AC, DC, 115 v

Stock No.	Description
5133-227-9658 (2) 5133-227-9659 (2) 5133-227-9660 (2) 5133-227-9664 (2)	Drill, twist, HSS, SS, 1/4 in. Drill - Twist SS 17/64 in. HS Drill - Twist SS 9/32 in. HS Drill - Twist SS 11/32 in. HS
5133-227-9666 (2) 5133-227-9668 (2) 5133-227-9670 (2)	Drill - Twist SS 3/8 in. HS Drill - Twist SS 13/32 in. HS Drill - Twist SS 7/16 in. HS
5133-227-9672 (2) 5133-227-9673 (2)	Drill - Twist SS 1/2 in. HS Drill - Twist SS 15/32 in. HS
5133-227-9692 (2) 5133-240-8443 (2)	Drill - Twist SS 5/16 in. HS Drill, twist, HSS, SS, 19/64 in. Countersink, HSS, SS, 1/4 in. dis., 3/8 in., dis body,
5133-255-4061	82 deg. incl angle
5133-255-4062	Gountersink - Steel SS 3/8 in. body 1/4 in. shank
5136-199-6741 (2)	Tap - Hand plug 5 40
5136-203-6218 (2)	Tap, thd cutting, HSS, hand, plug, 10-32, NF
5136-203-6506 (2) 5136-203-6508 (2)	Tap, thd cutting, HSS, hand, plug, 8-32, NC Tap, thd cutting, HSS, hand, plug, 10-24, NC
5136-221-6106 (2)	Tap, the cutting, HSS, hand, plug, 3/8-24, NF, RH
5136-228-1004 (2)	Tap - Hand plug 4 48
5136-228-1005	Tan - Hand ning 5 lili
5136-230-2778 (2)	Die, thd cutting, rd split, adj, 13/16 in. OD, 8-32, NC, RH
5136-237-8263 (2)	Die the cutting, rd split, act, 15/10 in. U., 5-20, Mr
51.36-239-2765 (2)	Die, thd cutting, rd split, adj, 13/16 in. OD, 4-48 NF, RH
5136-239-2766 (2)	Die, the cutting, rd split, adj, 13/16 in. OD, 5-ld, NF
5136-239-2767 (2)	Die - Round adj split 6 40 13/16 in. OD Die, thd cutting, rd split, adj, 13/16 in. OD, 8-36, NF, RH
5136-239-2768 (2) 5136-239-2769 (2)	Die, the cutting, rd split, adj, 13/16 in. OD, 10-32, NF, RH
5136-239-2774 (2)	Die - Round adj split 3 48 13/16 in. OD
5136-239-2775 (2)	Die. thd cutting, rd split, 13/16 in. OD, 4-40, NC, RH
5136-239-2776 (2)	Die, the cutting, rd split, adj, 13/16, in. OD, 5-40, NC, RH
5136-239-2777 (2)	Die - Round adi split 6 32 13/16 in. OD
5136-239-2779 (2)	Die, thd cutting, rd split, adj, 13/16 in. OD, 10-24, NC, RH
5136-262-3467 (2)	Tap, thd cutting, HSS, hand, plug, 4-40, NC, RH
5136-262-3946 (2)	Tap, thd cutting, HSS, hand, plug, 1-64, NC, RH
5136-262-3947 (2)	Tap - Hand plug 1 72
5136-262-3956 (2)	Tap, thd cutting, HSS, hand, plug, 2-56, NC, RH size range Tap, thd cutting, HSS, hand, plug, 2-64, NF, RH
51 36- 26 2-3 957 (2) 51 36- 26 2-3 958 (2)	Tap, the cutting, HSS, hand, plug, 3-48, NC, Ed
5136-262-3959 (2)	Tap, thd cutting, HSS, hand, plug, 3-56, NF, RH
5136-516-2948 (2)	Tap, thd cutting, HSS, hand, plug, 6-40, NF
5136-516-2950 (2)	Tap, thd cutting, HSS, hand, plug, 8-36, NF
5136-516-3373 (2)	Tap, thd cutting, HSS, hand, plug, 6-32, NC
5136-596-4247 (2)	Tap - HSS hand bottoming 3/8 24
5136-626-6709	Stock - Die 13/16 in. OD die
5140 -251- 1534	Holder - Drill metal folding SS 29 drl 1/16 to 1/2 in.
5140-277-8836	Case, twist drill, 60 SS drl No. 1-60
5140-490-3835	Chest - Tool machinists 20 x 8-1/2 x 13 in. Gage, twist drill and drill rod, 1-60 range
5210-221-1893	Gage, depth, rule, 6 in. 1g, rule grad 32nd and 64th in.
5210-221-1900	nate noberie intel o vie rel inte Bren bring and and

Stock No.	Description
5210-221-1936	Caliper, micrometer, outside, thousandths of in. units, 5-6 in. range, ratchet stop
5210-223-9600	Level and plumb, wood, 18 in. lg o/a
5210-265-7453	Tap, measuring, steel, 6 ft mex. grad lgth
5210-640-0953	Indicator, dial, .025 in. range, .001 in. rad, 0-5-0 dial mks
5210-640-1160	Gage, twist drill and drill rod, 61-80 range
62 30- 28 3- 930 7 (4)	Light, desk, w/sw, med screw base lamp, 1 lamp, toggle sw, lamp posn adj by swivel joint, 26-3/4 in.rad, equipped w/integral securing device for horiz surf. mtg, 1 steel reflector, wired w/cable assy 6 ft 1g
6230-299-7693 (8)	Lamp Assy - Electric fluor desk adj arm clamp type 2 lamp reflector 18 in. 15 w 110 v 60 cyc
6675-526-8660	Straightedge - Steel bevel edge 18 in.
6675-526-8685	Straightedge - Steel bevel edge 12 in.
7910-254-4956(b)	Cleaner, vacuum vert, tank type w/wheels
3460-180-0837 (2)	Clamp, par, toolmaker's 3/4 in. max jaw open (RS 7900-099220)
3460-180-0839 (2)	Clamp, par toolmaker's 1-3/4 in. max jaw open (RS 7900-099300)
3460-180-0840 (2)	Clamp, par, toolmaker's, 2 in. max jaw open (RS 7900-099320)
3460-243-1956	Dog, lathe, bent tail, 3/4 in, cap. (RS 7900-231800)
3460-243-1957	Dog, lathe, bent tail, 1 in. cap. (RS 7900-231850)
3460-243-1958	Dog, lathe, bent tail, 1-1/2 in. cap. (RS 7900-232050)
3460-517-5375	Holder, cutting tool, turning, SS, sq cutter, 1/h in. wd (RS 7900-448290)
3460-517-5380	Holder, cutting tool, turning, offset, sq cutter 5/16 in. wd, 5/16 in. thk (RS 7900-147260)
3460-517-5384	Holder, cutting tool, thd, IH offset, shank, 3/8 in. wd, 7/8 in. h, 5 in. h (RS 7900-446800)
668 0-4 90-34 34 7CAD	Tachometer, mech, hand held, 0-1000 rpm (RS 7CAD-797300)
6760-240-7416	Meter, photo. exposure, type LM-46 (RS 6760-597-5778)
7900-073500	Caliper - Inside micrometer .200 to 1 in. grad .001
5830-222-7663	Intercommunication station, wire transmission, ampl not incl, incl call switch
6150-279-6342	Cable assy, power elec, 2 conduc, 16 AWG, 100 ft 1g o/a, conn plug, four outlet recpt
6230-299-7693 (3)	Light, desk, w/switch, 110 v, ac, accommodates 2 lamps
6675-183-6487	T-Square, fixed hd, 14-16 in. 1g hd, 42 in. blade
6675-245-5555	Scale, drafting, two bevel, alum. alloy, 18 in. grad 1g
6675-526-8521	Drawing board and trestle, 60 in. 1g
6675-641-3529	Drafting instrument set, set 1
7110-281-1469 (6)	Chair, rotary, steel frame, back and seat upholstered, foam rubber
7110-286-3797 (2)	Filing cabinet, cap size design, steel E finish, non- sectional type, w/o base, 5 drawers h, 1 drawer wd, o/a dim. 28 in. d, 57-1/2 in. h, 18 in. wd
7430-281-6978	Typewriter, port., upper and lower case characters, AS keyboard, no. of keys A/A, elite style
7520-224-7593 7520-281-5895	Sharpener - Pencil draftsmans single or var aperture Stapler, paper fastening, office, desk style, designed for preformed staples, 1/2 in. crown width, 1/4 in. leg length

Stock No.	Description
7520-527-2348	Trimmer, paper, drop knife, w/guide lines parallel and at R angle to cutting edge, w/movable trimming guide, 1/2 in. spacing, bed material wood, 2h in. lg, 2h in. wd paper dim.
3920-11:1-7230	Truck, hand, shelf, 3 fixed steel shelves, tray type, 11 in. spacing, 4 casters, 2 swivel, 2 rigid type, solid rubber tires, steel chassis
6650-526-8247 (3)	Stereoscope, lens, pocket type, 2-1/2 power magnification
7195-691-3492 3920-222-1024	Table - Layout 4 x 8 ft x 36 in. high Truck, hand, two-wheeled, general utility type, 52 in. 1g side rails, str crossbars, 2 curved steel handles, solid rubber tires
3920-329-4283	Truck - platform hand non-tilt type wood 60 in. 1g x 36 in. wd push bar handle rubber tires 2 wheel 2 casters
3920-543-6026	Truck, hand, lift, pallet type, 4000 lb. cap., hyd lift
4110-277-8928	Cabinet, frozen food, 18 cu. ft storage cap., w/o ice cube making equip
5110-142-4999	Saw, hand, crosscut, 24 in., 11 point
5110-595-8400	Knife, craftman's, stencil etching and cutting, remov blade Hammer, hand, carpenter's, nailing, curved-claw, 13 oz
5 120-187-101 5 5 120-2 44-9 3 85	Puller, nail, side joint
7105-269-8463 (8)	Chair, folding, metal frame, tubr type, metal seat, metal
1103-203-0403 (07	back, medium gray color, front-to-back folding
7105-269-9275 (2)	Table, folding legs, solid top, wood, E finish, 36 in. lg, 24 in. wd
7110-267-1996 (6)	Desk, field, hinged lid, h plywood drawers, 1 storage compt
7125-269-8534 (2)	Cabinet, storage, steel, gray, E finish, w/lock, 18 x 78 x 36 in. o/a dim., 4 adj shelves, 2 door
7520-263-3425	Perforator, paper, desk, rd perforations, w/movable paper guide, adj, 3 punches, 13/32 in.dia
7520-285-2380	Dispenser, gummed tape, lever oper type, adj or nonadjustable moisture cont, A/A lgth of tape dispensed, 8 in. max outside roll dia, 4 in. max wd tape
3432-223-2530	Soldering iron, elec, 2-1/8, 1-5/16 in. dia, 110 v, 25 w, ac
3540-234-6742	Sealer, steel strapping, hand, 5/8 in.
4310-693-2652	Compressor - Power or type MB-9
4940-396-1664	Spray gun, paint, nonbleeder type, designed for hand oper, ext-mix type air cap., 10.68 cfm rated at 60 lb press.
	max. air consumption 1/4-18 air hose conn thd size, 3/8-18
5110-142-4947	fluid hose conn thd size NPSF Frame, hand, hacksaw adj 8 in. to 12 in.
5120-180-0907	Clamp, C, 3 in. nom size 1 7/8 in. deep throat
5120-180-0908 (5)	Clamp, C, 4 in., 2-1/4 in. d throat, lt serv
5120-180-0909	Clamp. G. 6 in., 2-3/4 in. d throat, lt serv
5120-184-8602	Wrench, box, angular offset dbl hd, 12 point, 5/16, 3/8 in. size
5120-184-8603	Wrench, box, angular offset, dbl hd, 12 point, 3/6, 7/16 in. size
5120-184-8615	Wrench, open end, fixed, single head style, nonsparking and non-magnetic
5120-184-8671	Wrench, box, dbl offset hd, 12 point, 5/8, 11/16 in. size
5 120-1 84 - 86 72	Wrench, box, dbl offset hd, 12 point, 3/4, 7/8 in. size

Stock No.	Description
5120-184-8673 5120-184-8674 5120-184-8676	Wrench, box, dbl effect hd, 12 point, 7/8, 15/16 in. size Wrench, box, dbl offset hd, 12 point, 15/16, 1 in. size Wrench, box, angular offset dbl hd, 12 point, 1-1/4, 1-5/16 in. size
5120-184-8677 5120-184-8678 5120-204-0672	Wrench, box, dbl offset hd, 12 point, 1-1/4, 1-3/8 in. size Wrench, box, dbl offset hd, 12 point, 1-7/16, 1-1/2 in. size Screwdriver, ratchet, R angle offset, RH and LH, 3-51/64 in. 1g, 2 blades
5120-223-6943	Extractor, screw, str fluted, w/sliding nut, 7/16 in. screw size rating. No. h
5120-245-4227 5120-272-4284 5120-277-1484 (2)	Vise, machinist's, swivel base, 4-1/2 in jaw, 5-1/2 in. open Extractor, cotter pin, 6 in. Wrench, pipe, adj jaw, 8 in. 1g, 1/4 to 3/4 in.
5120-277-1486 (2) 5120-293-0487	Wrench, pipe, adj jaw, lu in. lg, 1/2 to 1-1/2 in. Hammer, hand, inserted face, 1-1/4 lb, plas, 1-1/2 in. dia. face
51 20- 596 -7 466 52 10-263- 03 7 6 62 30- 299 - 5 71 4	Etcher, elec, vibr type, ac, 60 cyc, s ph, 110 v Dividers, mech, spring type, 8 in. Flashlight, tapered tubr case, holds two 1-1/2 v bat., plas, colorless glass lens, G 3-1/2 miniature screw base lamp,
7340-162-2205	nonfocusing, 6-1/2 ft flex. exten, type A-5A Knife, pocket, w/clevis, can opener, scdr, bottle opener, 2 blades
7490-164-0541 6645-566-5537	Stencil cutting mach, hand oper, 1/2 in. character h Timer, interval, elec, 110 v, 60 cyc, ac, sync mtr, equipped with internal expiration signalling device, 60 min cap., P/N 168
6740-201-0958	Sink, photo processing temp cont, cabinet type, 72 in. lg, 26 in. wd. 6 in. d
6740-558-5861	Tray, process. Photo. Corr. resist. steel 17-1/2 x 21-1/2 x 2-3/4 in.
6760-597-5777 7310-641-6041	Densitometer, visual, transmission, 0 to 3.0 scale Hot plate, elec, 1 wire wound covered unit, 1 rotary type sw with 3 heating speeds, 115-125 v ac, 60 cyc, 1 ph, 2000 w
7520-162-6178	Sharpener, pencil, general writing point cut, w/variable aperture
6685-490-2469 8900-922000	Psychrometer, 20-120 deg. F Tank - Photographic developing 35mm film SS w/dbl reel for simultaneous development of two 5 ft lgth of 35mm film